PR03 Series













PREMIUM HEVC ENCODER OVER BONDED CELLULAR **NETWORKS**

The PRO3 Series is our flagship mobile video encoder & transmitter solution designed for live video producers and news gathering professionals looking for contribution performance from any location

With its large set of professionnal audio and video interfaces, the PRO3 Series supports the best state-of-the-art H.265/HEVC hardware encoder by offering premium video quality with less data usage, and low end-to-end latency (down to 0.5 sec). The widely adopted H.264/AVC video format is supported as well for compliancy with deployed infrastructures.

It features 8 embedded world-wide compliant cellular 3G/4G-LTE modems with a high efficiency patented custom antenna array. All are available in the unit, but the device can also be remotely connected to AVIWEST's QUAD Antenna external antennas for strengthening the signal transmission in critical environment. Additional links such as built-in Wi-Fi and Dual Gigabit Ethernet for streaming over LAN/WAN, BGAN, GX or Ka band Satellite are also natively supported.

With its high versatility and low consumption (up to 4 hours with external battery), the PRO3 Series is the ideal companion for on-the-go video professionals that need robust and reliable solution, with the ultimate performance and picture quality.



The PRO3 Series has been designed with ease-of-use in mind, the user-friendly intuitive interface allows broadcasting live videos in 2 touch screen taps.



Available in a compact ruggedized

enclosure, the PRO3 Series offers standard V-Mount or Gold-Mount plate for direct mounting on professional cameras, but also comes with in a smart designed & compact backpack.



HIGH PERFORMANCE

implementing the H.265/HEVC state-of-the art hardware encoder in a compact design enclosure, the PRO3 Series enables video professionals to provide seamless high quality news and event coverage.



ANY NETWORKS

Leveraging AVIWEST's SafeStreams technology, an intelligent IP bonding stack and powerful contribution network protocols, the PRO3 Series ensures the delivery of live video even in the midst of unpredictable and unmanaged network conditions.

PRODUCTS COMPARISON CHART

	PR0 380	PR0 340
Internal cellular modems	8	4
Internal High Efficiency Antennas	8	4



files for transmitting.

devices (SD card or USB key) over bonded IP

networks. You can select all or a subset of

MAIN FUNCTIONS

LIVE & AUTO-RECORD

Broadcast premium quality video live over bonded IP networks: 3G/4G-LTE, Ethernet, Wi-Fi, and satellite networks such as BGAN, GX and Ka Band. Combined with the automatic record feature, you can simultaneously record this live on the pluggable SD card with different resolution and bitrate to ensure an optimal and constant video quality.

RECORD & PROGRESSIVE FORWARD

Record broadcast-grade quality video on the SD card, and optimize your time by forwarding the file progressively whereas the record is still in progress. This forward approach enables fast and error-free video delivery.

MAIN SPECIFICATIONS

HD: 1080p25/29.97/30/50/59.94/60.

1080i50/59.94/60,

720p50/59.94/60

H.265/HEVC 4:2:0, 8-bit

H.264/AVC 4:2:0, 8-bit Dynamic resolution adjustment

200 Kbps to 20 Mbps Constant Bitrate (CBR)

Variable Bitrate (VBR)

SDI, HDMI

SD: PAL. NTSC

ADVANCED FEATURES

AVIWEST SafeStreams technology Sub second glass-to-glass latency (down to 500ms) Dual encoding for simultaneous Live & Record

MPEG-2 TS recording Geolocation (GPS and Galileo) Intercom / IFB

INTERFACES

1 x 3G-SDI input (BNC) 1 x 3G-SDI output (BNC) 1 x HDMI 1.4 input,

1 x HDMI 1.4 output 2 x RJ-45 Ethernet 1 x USB 3.0 (type-A) 8 MCX connectors (for AVIWEST QUAD antenna solution) 1 x mini XLR (for IFB / intercom)

2 x mini XLR balanced (for analog audio)

1 x SD card slot 8 x micro SIM slots

AUDIO

VIDEO

STANDARDS

ENCODING

BITRATES

INPUTS

ENCODING AAC-LC BITRATES 32 Kbps to 256 Kbps MODE Mono, Dual Mono or Stereo 2.0 DENSITY Up to 4 channels Embedded (SDI, HDMI), Analog (L/R) INPUTS

CONTROL & MONITORING

On screen display Web GUI (through laptop, smartphone, etc.)
From AVIWEST MANAGER Management System
From AVIWEST STREAMHUB Transceiver

NETWORK CONNECTIONS

INTEGRATED MODEM

- 8 x 3G/4G-LTE modems with
 - Internal high efficiency antennas
 - External high efficiency antennas (AVIWEST QUAD antenna arravs)

ETHERNET Gigabit Ethernet port

portable satellite (BGAN, GX, Ka Band)

WI-FI

Dual band Wi-Fi modem 802.11b/g/n/ac (MIMO 2.4GHz and 5 GHz]

· Client & Hot Spot modes

- High-efficiency antenna

POWER

DC input 12V-24V (XLR input hot swap) POWER SUPPLY

External battery with V-mount or Gold-mount plates

CONSUMPTION 4 hours with battery (90Wh)

PHYSICAL

DIMENSIONS (W x H x D)

24.5 cm x 5.5 cm x 12.8 cm [9.44" x 1.96" x 4.72"]

WEIGHT 1.35 Kg / 2.97 lbs

OPERATION -10°C to 45°C (14°F to 113°F) TEMPERATURE

SYSTEM OVERVIEW

