

LARK 150

CLIP-ON WIRELESS MICROPHONE SYSTEM

LARK 150
INSPIRATION OF SOUND



- PRO SOUND QUALITY
- 100M STABLE RANGE
- < 5MS LATENCY
- ULTRA COMPACT
- MONO/STEREO SAFETY MODES
- PORTABLE CHARGING CASE
- TWO-WAY MUTE
- 2TX & 1RX COMBO
- REAL-TIME MONITORING
- OLED DISPLAY

Parameters

Interfaces	TX: 3.5mm Audio Input Port Charging/Upgrading Contacts / RX: 3.5 mm TRS Output Interface 3.5mm Headset Interface Charging/Upgrading Contacts / Charging Case: USB Type-C Interface
Frequency Bandwidth	2.4GHz AFH
Built-In Mic	Polar Pattern: Omnidirectional / Frequency Response: 20Hz~20KHz
Lavalier Mic	Polar Pattern: Omnidirectional / Frequency Response: 20Hz~20KHz
Reference Audio Input Level	-65 dBV
Maximum Input Sound Pressure Level	100dB SPL (1KHz@1m)
Dynamic Range	100 dBA
Polar Pattern	Omnidirectional
Audio Output Level Change Range	21-State: 45dB
Transmission Latency	5ms
Battery Mode	TX: 200mAh (0.76Wh) / RX: 530mAh (1.96Wh) / Charging Case: 3350mAh (12.16Wh)
Battery Life	TX: 4.5h / RX: 7.5h / Charging Case: About 2.5 times (Charge 2 TX and 1 RX at the Same Time in Full Charged States)
Charging Time	TX: 1.5h / RX: 2h / Charging Case: 2.5h
Firmware Upgrade Method	Pc
Dimensions	TX: (L*W*H) 37*37*17.5mm / RX: (L*W*H) 67*41*20.5mm / Charging Case: (L*W*H) 121*61*43.5mm
Weight	TX: 20.5g / RX: 51g / Charging Case: 227.5g

Packing List

- Charging Case x1
- Transmitter x2
- Receiver x1
- Furry Windshield x2
- 3.5mm TRS Cable x1
- USB Type-A to Type-C Cable x1
- Lavalier Microphone x1
- User Guide x1
- Storage bdg x1

*Please subject to actual shipment as the standard if any difference in accessories.

Reliable Wireless Experience

www.hollyland-tech.com

